

In the claims:

1. (currently amended) A motor-driven compass saw machine (1), having a housing (2) that contains a longitudinally moving lifter rod (4), which supports a saw blade (3), and an oscillation mechanism that is able to impart a variable oscillation stroke, which is oriented lateral to the longitudinal motion, to the saw blade (3),

wherein ~~it is possible to automatically adjust~~ means is provided for automatically adjusting the oscillation stroke smoothly between the maximum and minimum stroke during the sawing process, as a function of the pressure of the saw blade (3) against a work piece to be sawn.

2. (previously presented) The compass saw machine as recited in claim 1, whose oscillation mechanism has a roller lever (5) that is disposed in the housing (2), can rotate around a horizontal first axis (50), and supports a roller (51) that remains in contact with the saw blade (3) and can rotate around a horizontal second axis (55), and whose oscillation mechanism has a fork lever (6) that periodically deflects the roller lever (5).

3. (original) The compass saw machine as recited in claim 2, wherein the oscillation mechanism includes a spring element (53) that is disposed between the housing (2) and the end (52) of the roller lever (5) oriented

away from the roller and cooperates with a component parallel to the deflection direction of the fork lever (6).

4. (original) The compass saw machine as recited in claim 3, wherein parallel to the spring element (53), a damping device (54) is disposed between the housing (2) and the end (52) of the roller lever (5) oriented away from the roller.

5. (previously presented) The compass saw machine as recited in claim 2, wherein underneath the roller lever (5), in the region of its end (52) oriented away from the roller, a first stop (20) is provided on the housing (2).

6. (previously presented) The compass saw machine as recited in claim 2, wherein above the roller lever (5), in the region of its end (52) oriented away from the roller, a second stop (21) is provided on the housing (2).

7. (original) The compass saw machine as recited in claim 6, wherein the second stop (21) can be set to various distances from the roller lever (5).

8. (original) The compass saw machine as recited in claim 7,

wherein the second stop (21) can be manually set to discrete distances from the roller lever (5).

9. (previously presented) The compass saw machine as recited in claim 2, wherein the saw blade (3) is pressed against the roller (51) by a compression spring (30) whose compression spring force ( $F_2$ ) is weaker than a spring force ( $F_1$ ) of a spring element (53).

10. (previously presented) The compass saw machine as recited in claim 9, wherein a deflection of the roller lever (5) only occurs an advancing force ( $F_3$ ) of the compass saw machine (1) is greater than the difference between the spring force ( $F_1$ ) and the compression spring force ( $F_2$ ).

Claim 11 cancelled.